

An investigation of flow characteristics in slope siphon drains

边坡高扬程虹吸排水管流态特征研究

Cite this as: Yue-liang Cai, Hong-yue Sun, Yue-quan Shang, Xiao-liang Xiong, 2014. An investigation of flow characteristics in slope siphon drains. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 15(1):22-30. [doi:10.1631/jzus.A1300178]

Main goal of this paper

The flow characteristics of siphon drainage are significantly influenced by the hose diameter. In slope engineering, a 3.6 mm polyurethane (PU) hose is recommended for siphon drainage to maintain its long-term effectiveness.

Main observation in model test

Water flows in the form of a wall pressing flow in a large diameter siphon hose (e.g., larger than 5.0 mm) under low flow velocity, which leads to discontinuous siphon drainage. However, water flows in the form of an integral slug flow in a small diameter siphon hose (e.g., smaller than 4.0 mm) under low flow velocity, which leads to continuous siphon drainage.





Fig. 4 Three types of flow at the vertex of hoses
(a) Wall pressing flow; (b) Slug flow; (c) Incomplete slug flow

Computational model and results



The threshold of hose diameter can be theoretically obtained. Wall pressing flow is more likely to be generated in the lower hose when $r > r_c$, while complete slug flow can be generated when $r < r_c$.

$$r_c = \sqrt{\sigma_{lg} \cos \theta / \rho g}$$

PU hoses with a diameter of 3.6 mm are recommended, to guarantee the long-term operation of siphon drainage.

Fig. 6 Surface shapes for hoses with different diameters
(a) $r > r_c$; (b) $r \leq r_c$