

Na-e Zheng, You Zhou, Han-ying Hu, Sheng Wang, 2014. Sub-channel shared resource allocation for multi-user distributed MIMO-OFDM systems. *Journal of Zhejiang University-SCIENCE C (Computers & Electronics)*, 15(11):1048-1057.

[doi:[10.1631/jzus.C1400049](https://doi.org/10.1631/jzus.C1400049)]

Sub-channel shared resource allocation for multi-user distributed MIMO-OFDM systems

Key words: MIMO-OFDM, Multi-user, Resource allocation, Sub-channel shared, Signal to leakage plus noise ratio (SLNR)

Corresponding author: Na-e ZHENG

E-mail: zhengnaecshz@163.com

Motivation

- Well-controlled resource allocation is crucial for promoting the performance of multiple input multiple output orthogonal frequency division multiplexing (MIMO-OFDM) systems
- Recent studies have focused primarily on traditional centralized systems or distributed antenna systems (DAS), and usually assume that one sub-carrier or sub-channel is exclusively occupied by one user, which means they cannot make full use of space division multiple access (SDMA) in MIMO systems well and have a limited capacity performance

Main idea and method

- To promote system performance, a sub-channel shared resource allocation algorithm for multi-user distributed MIMO-OFDM systems is proposed
- Each sub-channel can be shared by multiple users in the algorithm, which is different from previous algorithms
- The algorithm assumes that each user communicates with only two best ports in the system. On each sub-carrier, it allocates a sub-channel in descending order, which means one sub-channel that can minimize signal to leakage plus noise ratio (SLNR) loss is deleted until the number of remaining sub-channels is equal to that of receiving antennas

Major results

- Simulations show that compared to other algorithms, our proposed algorithm has better capacity performance and enables the system to provide service to more users under the same capacity constraints