



Editorial

<https://doi.org/10.1631/jzus.A22FCSV1>



Practice of flow control and smart valves

Jin-yuan QIAN^{1,5}✉, Wei WU²✉, Min CHENG³✉, Jun-hui ZHANG^{4,5}✉

¹Institute of Process Equipment, College of Energy Engineering, Zhejiang University, Hangzhou 310027, China

²School of Mechanical Engineering, Beijing Institute of Technology, Beijing 100081, China

³School of Mechanical and Vehicle Engineering, Chongqing University, Chongqing 400044, China

⁴Institute of Mechatronics and Control Engineering, Zhejiang University, Hangzhou 310027, China

⁵State Key Laboratory of Fluid Power and Mechatronic Systems, Zhejiang University, Hangzhou 310027, China

Introduction

The usual metaphors of “heart” and “throat” indicate the importance of pumps and valves in industrial systems including petroleum, chemical, metallurgy, aviation, and aerospace. With the continuous penetration of the industrial internet, the miniaturization, digitization, multi-functionalization, and systemization of valves have become very important (Si et al., 2020; Chang et al., 2021; Pang et al., 2021; Bonilla et al., 2022; Yuan et al., 2022; Zhao et al., 2022). Flow control, especially smart flow control, is one of the critical issues in the field of pump and valve research related to the process requirements of piping systems (Jin et al., 2020; Lyu LT et al., 2021; Fiderek et al., 2022; Zhang et al., 2022). The importance of smart flow control is greatly increased when valves operate at high temperatures and in high-pressure environments, or in novel fluids such as nanofluids, compressed hydrogen, and superheated steam (Qian et al., 2020a, 2020b; Ji et al., 2021; Lin et al., 2021; Lyu F et al., 2021). Online fault detection is an important means of intelligent operation and maintenance of pumps and valves; it not only ensures their performance requirements, but also prolongs their service life (di Capaci and Scali, 2018; Zhou et al., 2018;

Tang et al., 2019; Yu et al., 2020; Vailati and Goldfarb, 2021; Pedersen et al., 2022; Peng et al., 2022). Therefore, it is urgent to develop intelligent valves with adjustment accuracy, fast response, accurate parameter feedback, convenient remote operation, instant online fault diagnosis, and fail-safe capability. As this field has attracted more and more attention in recent years, it has achieved remarkable development. However, it is worth noting that there is no dedicated publication or issue devoted to these aspects.

This special issue contains original and hitherto unpublished work on the practice of flow control and smart valves. Focal points of the issue include, but are not limited to, innovative applications of: (1) optimized design of novel valve cores, valve bodies, and flow channels; (2) improved precise control of flow, valve target pressure, and reduction of noise and vibration in piping systems; (3) development of novel fluid valves for use with nanofluids, superheated steam, pressurized hydrogen, and so on; (4) development of sensing systems for parameter feedback, remote operation, and fault diagnosis.

We have invited renowned scientists in the field to share their expertise and perspectives. These cover the various topics mentioned: (1) on-line fault diagnosis of pumps and valves; (2) on-line performance monitoring of pumps and valves; (3) improvement of pumps and valves under extreme conditions, in respect of dynamic performance, seal performance, and adjustment accuracy.

Lin et al. (2022) analyze the seal performance of hydrogenated nitrile butadiene rubber (HNBR) gaskets in a charge valve seal pair by finite element analysis. A nonlinear finite element analysis model is established

✉ Jin-yuan QIAN, qianjy@zju.edu.cn

Wei WU, wuweijing@bit.edu.cn

Min CHENG, chengmin@cqu.edu.cn

Jun-hui ZHANG, benzjh@zju.edu.cn

Jin-yuan QIAN, <https://orcid.org/0000-0002-5438-0833>

Received Apr. 5, 2022; Revision accepted Apr. 12, 2022;

Crosschecked Apr. 26, 2022

© Zhejiang University Press 2022

to dynamically analyze the seal contact characteristics under different pre-compression amounts, seal widths, and hydrogen pressures. The contact pressure on the sealing surface increases with the increase in pre-compression. When the seal width increases, so does the contact pressure on the seal faces and the width of the separation area between the seal faces.

Shi et al. (2022) propose a heterogeneous sensor information fusion method to enhance the fault expression ability of the feature set, so that the diversification of fault types (electromagnetic faults and mechanical faults) can be characterized. The personalized weighting method (using the entropy weighting method and attention mechanism) used in the article enhances the effective signal and weakens the interference source. This method can achieve a higher fault diagnosis accuracy under severe working conditions.

Zhong et al. (2022) propose an on/off pilot technique using two independent high-speed on/off valves (HSVs) to replace conventional pilot-operated proportional valves. Through the fast-switching characteristics of HSV, the dead zone of the pilot stage is avoided, and the dynamic response performance of the main valve is improved. The feasibility of switching the pilot technology scheme is proved through theoretical analysis and experimental demonstration.

Kang et al. (2022) use a whole-valve transfer function model to analyze the mechanism and evaluation of the operating point drift when a thermal effect acts on the servo valve. The asymmetrical relationship of the armature-nozzle combination is an important reason for the thermal effect causing drift of the operating point. Differences in structural parameters and fluid medium properties at different temperatures lead to nonlinear changes in the operating point.

Sun et al. (2022) propose a fault diagnosis method based on mathematical model (MM) imputation and a modified deep residual shrinking network (MDRSN), which improves the accuracy in missing data estimation and fault diagnosis. Multiple fault time-series samples of the regulating valve at different opening degrees are collected. The MM imputation model is used to supplement the incomplete data set, and an improved residual shrinkage network is used to diagnose the faults of the control valve under different conditions.

Lu et al. (2022) analyze the statically indeterminate structure of an unloading valve and quantitatively

calculate the amount of fretting wear of a valve in a gasoline direct injection high-pressure pump. A fretting wear test system is constructed, and the test data of ball valve fretting wear is obtained. Through theoretical derivation, a statically indeterminate force model of ball valve fretting wear is constructed, and the key fretting parameters required for simulation calculation are obtained. The wear formula suitable for finite element calculation is obtained by improving the Archard wear model, and a quantitative numerical calculation model of ball valve fretting wear is constructed by combining the iterative acceleration calculation method and grid adaptive technology.

Mao et al. (2022) propose a single-layer and stacked electrohydrodynamic (EHD) pump to improve the output pressure and flow of an electric hydraulic pump. The bendable and twistable electrohydraulic pump is realized by digital manufacturing, and the designed and processed electro-hydraulic pump is used to drive the eccentric actuator. The output pressure and flow of the superimposed electric hydraulic pump are measured experimentally and compared with the output pressure and flow of a single-layer electric hydraulic pump.

We believe this special issue will provide a forum for researchers and engineers to present and discuss recent developments in the practice of flow control and smart valves. We expect the selected papers will stimulate discussion among scientific researchers, and we hope that they will bring new inspiration to readers of this journal.

Conflict of interest

Jin-yuan QIAN, Wei WU, Min CHENG, and Jun-hui ZHANG declare that they have no conflict of interest.

References

- Bonilla CA, Zanfei A, Brentan B, et al., 2022. A digital twin of a water distribution system by using graph convolutional networks for pump speed-based state estimation. *Water*, 14(4):514. <https://doi.org/10.3390/w14040514>
- Chang V, Xu YK, Zhang JQ, et al., 2021. Research on intelligent manufacturing development approach for China's local valve industry. *Smart and Sustainable Built Environment*, 10(2):293-321. <https://doi.org/10.1108/Sasbe-02-2020-0014>
- di Capaci RB, Scali C, 2018. Review and comparison of techniques of analysis of valve stiction: from modeling to smart diagnosis. *Chemical Engineering Research and Design*, 130:230-265.

- <https://doi.org/10.1016/j.cherd.2017.12.038>
Fiderek P, Kucharski J, Wajman R, 2022. Fuzzy regulator for two-phase gas-liquid pipe flows control. *Applied Sciences*, 12(1):399.
<https://doi.org/10.3390/app12010399>
- Ji X, Wang AC, Wei XH, 2021. Precision control of spraying quantity based on linear active disturbance rejection control method. *Agriculture*, 11(8):761.
<https://doi.org/10.3390/agriculture11080761>
- Jin ZJ, Qiu C, Jiang CH, et al., 2020. Effect of valve core shapes on cavitation flow through a sleeve regulating valve. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 21(1):1-14.
<https://doi.org/10.1631/jzus.A1900528>
- Kang J, Yuan ZH, Li JC, 2022. Mechanism analysis and evaluation of thermal effects on the operating point drift of servo valves. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):286-302.
<https://doi.org/10.1631/jzus.A2100464>
- Lin ZH, Li JY, Jin ZJ, et al., 2021. Fluid dynamic analysis of liquefied natural gas flow through a cryogenic ball valve in liquefied natural gas receiving stations. *Energy*, 226:120376.
<https://doi.org/10.1016/J.ENERGY.2021.120376>
- Lin ZH, Yu LJ, Hua TF, et al., 2022. Seal contact performance analysis of soft seals on high-pressure hydrogen charge valves. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):247-256.
<https://doi.org/10.1631/jzus.A2100395>
- Lu L, Xu YP, Li MR, et al., 2022. Analysis of fretting wear behavior of unloading valve of gasoline direct injection high-pressure pump. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):314-328.
<https://doi.org/10.1631/jzus.A2100685>
- Lyu F, Ye SG, Zhang JH, et al., 2021. Theoretical and simulation investigations on flow ripple reduction of axial piston pumps using nonuniform distribution of pistons. *Journal of Dynamic Systems, Measurement, and Control*, 143(4):041008.
<https://doi.org/10.1115/1.4048859>
- Lyu LT, Chen Z, Yao B, 2021. Advanced valves and pump coordinated hydraulic control design to simultaneously achieve high accuracy and high efficiency. *IEEE Transactions on Control Systems Technology*, 29(1):236-248.
<https://doi.org/10.1109/TCST.2020.2974180>
- Mao ZB, Asai Y, Wiranata A, et al., 2022. Eccentric actuator driven by stacked electrohydrodynamic pumps. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):329-334.
<https://doi.org/10.1631/jzus.A2100468>
- Pang JH, Zhang N, Xiao Q, et al., 2021. A new intelligent and data-driven product quality control system of industrial valve manufacturing process in CPS. *Computer Communications*, 175:25-34.
<https://doi.org/10.1016/j.comcom.2021.04.022>
- Pedersen HC, Bak-Jensen T, Jessen RH, et al., 2022. Temperature-independent fault detection of solenoid-actuated proportional valve. *IEEE/ASME Transactions on Mechatronics*, in press.
<https://doi.org/10.1109/TMECH.2022.3158483>
- Peng L, Han GQ, Pagou AL, 2022. Real-time anomaly detection methodology in the electric submersible pump systems. *Petroleum Science and Technology*, in press.
<https://doi.org/10.1080/10916466.2022.2048013>
- Qian JY, Wu JY, Gao ZX, et al., 2020a. Effects of throttling window on flow rate through feed-water valves. *ISA Transactions*, 104:393-405.
<https://doi.org/10.1016/j.isatra.2020.05.017>
- Qian JY, Hou CW, Mu J, et al., 2020b. Valve core shapes analysis on flux through control valves in nuclear power plants. *Nuclear Engineering and Technology*, 52(10):2173-2182.
<https://doi.org/10.1016/j.net.2020.03.008>
- Shi JC, Ren Y, Tang HS, et al., 2022. Hydraulic directional valve fault diagnosis using a weighted adaptive fusion of multi-dimensional features of a multi-sensor. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):257-271.
<https://doi.org/10.1631/jzus.A2100394>
- Si QR, Lu R, Shen CH, et al., 2020. An intelligent CFD-based optimization system for fluid machinery: automotive electronic pump case application. *Applied Sciences*, 10(1):366.
<https://doi.org/10.3390/app10010366>
- Sun F, Xu H, Zhao YH, et al., 2022. Data-driven fault diagnosis of control valve with missing data based on modeling and deep residual shrinkage network. *Journal of Zhejiang University-SCIENCE A (Applied Physics & Engineering)*, 23(4):303-313.
<https://doi.org/10.1631/jzus.A2100598>
- Tang HB, Yang WX, Wang ZC, 2019. A model-based method for leakage detection of piston pump under variable load condition. *IEEE Access*, 7:99771-99781.
<https://doi.org/10.1109/ACCESS.2019.2930816>
- Vailati LG, Goldfarb M, 2021. A method for mass flow and displacement estimation in a pneumatic actuation system using valve-based pressure sensing. *IEEE/ASME Transactions on Mechatronics*, 26(1):235-245.
<https://doi.org/10.1109/Tmech.2020.3011348>
- Yu H, Li HR, Li YL, 2020. Vibration signal fusion using improved empirical wavelet transform and variance contribution rate for weak fault detection of hydraulic pumps. *ISA Transactions*, 107:385-401.
<https://doi.org/10.1016/j.isatra.2020.07.025>
- Yuan CG, Plummer A, Pan M, 2022. Switching characteristics of a high-speed rotary valve for switched inertance hydraulic converters. *Proceedings of the Institution of Mechanical Engineers, Part I: Journal of Systems and Control Engineering*, in press.
<https://doi.org/10.1177/09596518221082445>
- Zhang F, Zhang JH, Cheng M, et al., 2022. A flow-limited rate control scheme for the master-slave hydraulic manipulator. *IEEE Transactions on Industrial Electronics*, 69(5):4988-4998.
<https://doi.org/10.1109/Tie.2021.3084175>
- Zhao KP, He T, Wang CL, et al., 2022. Lubrication characteristics analysis of slipper pair of digital valve distribution axial piston pump. *Advances in Mechanical Engineering*,

14(3):1-15.

<https://doi.org/10.1177/16878132221085442>


Zhong Q, Xu EG, Jia TW, et al., 2022. Dynamic performance and control accuracy of a novel proportional valve with a switching technology-controlled pilot stage. *Journal of Zhejiang University-SCIENCE A (Applied Physics &*

Engineering), 23(4):272-285.

<https://doi.org/10.1631/jzus.A2100463>

Zhou CJ, Ma J, Wu JD, 2018. Fault diagnosis of check valve based on CEEMD compound screening, BSE and FCM. *IFAC-Papersonline*, 51(21):323-328. <https://doi.org/10.1016/j.ifacol.2018.09.440>

Introducing Guest Editor-in-Chief and Guest Editors:



Jin-yuan QIAN is presently Associate Professor in Institute of Process Equipment, College of Energy Engineering, Zhejiang University, China since 2018. He received B.S. and Ph.D. degrees both in Chemical Process Equipment from Zhejiang University in 2011 and 2016, respectively. He was a joint Ph.D. student at TU Bergakademie Freiberg, Germany from 2013 to 2014, and a Postdoctorate Researcher in the Department of Energy Sciences, Lund University, Sweden from 2016 to 2017. He is an Editorial Board Member of *Micromachines*, and Technical Editor of *Valves*. His research interests include valves, flow control, and computational fluid dynamics. He has coauthored about 50 papers in international journals and conferences, and is author of over 20 patents.



Wei WU received his Ph.D. degree in mechanical engineering from Beijing Institute of Technology, China in 2010. He has been Associate Professor with the School of Mechanical Engineering, Beijing Institute of Technology since 2013. His specialty mainly focuses on vehicular dynamics, fluid power, and heat transfer. His research interests include hybrid propulsion of high-speed off-road vehicles and two-phase flow. He has published more than 60 journal papers, in which 32 papers were indexed by the Scientific Citation Index (SCI). He has authored or coauthored more than 40 National Invention Patents with 33 granted.



Min CHENG received his Ph.D. degree from Zhejiang University in 2015 and is currently an Associate Professor and Doctoral Supervisor in the School of Mechanical and Vehicle Engineering, Chongqing University, China. He is a senior member of the Chinese Society of Mechanical Engineering and an Editorial Board Member of *Chinese Hydraulics & Pneumatics*. His research interests are energy-saving electro-hydraulic control systems, advanced motion control strategies, and human-machine interfaces of heavy-duty hydraulic robots. He has won the China Machinery Industry Science and Technology Award (first class, 2021) and the Excellent Paper Award of the China Mechanical Engineering Society. He has published more than 50 journal and conference papers and authored or applied for over 15 patents.



Jun-hui ZHANG received B.S. and Ph.D. degrees in mechatronics from Zhejiang University, China in 2007 and 2012, respectively. He is currently a Researcher with the Institute of Mechatronics and Control Engineering, Zhejiang University. He has authored or coauthored more than 50 papers indexed by SCI and applied for more than 20 National Invention Patents with 18 granted. He is supported by the National Science Fund for Excellent Young Scholars. His research interests include high-speed hydraulic pumps/motors and hydraulic robots. He is a Technical Editor of *IEEE/ASME Transactions on Mechatronics*.